



SOLIBRI AUTORUN EXAMPLE USECASES

Example use case 1. Create a federated model automatically. (keep your .smc model up-to-date with the newest ifc's)



Example use case 2. Open ifc's, classifications* and rulesets*, run checkings and report issues directly with Autorun.



* If a role is selected in a previous Solibri session, the resources (classifications and rulesets) are opened by default and they are not required to be opened with Autorun.

Example use case 3. Open a .smc model*, update new ifc's, run checkings, report issues and save the model. (keep your .smc model and found issues up-to-date)



* If the .smc model already contains the resources (rulesets, classifications) they are not required to be opened again

Example use case 1. Create a federated model automatically. (keep your .smc model up-to-date with the newest ifc's)

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<batch name="Simple Batch" default="root">
  <!-- This is the starting task -->
  <target name="root">

    <openmodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\models\Solibri model.smc" />

    <updatemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri Building.ifc"
      with="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri Building.ifc"/>

    <updatemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri Building Structural.ifc"
      with="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri Building Structural.ifc"/>

    <updatemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Ground_Floor_Vent.ifc"
      with="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Ground_Floor_Vent.ifc"/>


    <updatemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\First_Floor_Vent.ifc"
      with="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\First_Floor_Vent.ifc"/>

    <updatemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Second_Floor_Vent.ifc"
      with="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Second_Floor_Vent.ifc"/>

    <savemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\models\Solibri model.smc" />

    <exit />
  </target>
</batch>
```

Text highlighted in red
needs to be defined in
the .xml file by the user



Example use case 2. Open ifc's, classifications* and rulesets*, run checkings and report issues directly with Autorun.

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<batch name="Simple Batch" default="root">
  <!-- This is the starting task -->
  <target name="root">

    <openmodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri building.ifc" />

    <openclassification
      file="C:\Users\Public\Solibri\SOLIBRI\Classifications\Building Elements - General.classification"/>

    <openruleset
      file="C:\Users\Public\Solibri\SOLIBRI\Rulesets\Architectural Rules\BIM Validation - Architectural.cset"/>

    <check />
    <autocomment zoom="TRUE" />

    <createpresentation />


    <bcreport file=" C:\Users\Public\Solibri\SOLIBRI\Samples\reports\Found issues.bcfzip" version="2" />

    <savemodel
      file=" C:\Users\Public\Solibri\SOLIBRI\Samples\models\Solibri model.smc" />

    <exit />

  </target>
</batch>
```

Text highlighted in red
needs to be defined in
the .xml file by the user



* If a role is selected in a previous Solibri session, the resources (classifications and rulesets) are opened by default and they are not required to be opened with Autorun.

Example use case 3. Open a .smc model*, run checkings, report issues and save the model. (keep your .smc model and found issues up-to-date)

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<batch name="Simple Batch" default="root">
  <!-- This is the starting task -->
  <target name="root">

    <openmodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\models\Solibri model.smc" />

    <updatemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri Building.ifc"
      with="C:\Users\Public\Solibri\SOLIBRI\Samples\ifc\Solibri Building.ifc"/>

    <check />
    <autocomment zoom="TRUE" />

    <updatepresentation />

    <bcfreport file="C:\Users\Public\Solibri\SOLIBRI\Samples\reports\Found issues.bcfzip" version="2" />

    <savemodel
      file="C:\Users\Public\Solibri\SOLIBRI\Samples\models\Solibri model.smc" />

    <exit />

  </target>
</batch>
```

Text highlighted in red
needs to be defined in
the .xml file by the user



* If the .smc model already contains the resources (rulesets, classifications) they are not required to be opened again



Thank you!

